INDEPENDENT

BATTERY CERTIFICATE

AVILOO
BATTERY DIAGNOSTICS

CERTIFICATE NUMBER: A9E97F5F-09F5-412C-BC96-6AC7C622E1C1

VEHICLE

BRAND: Tesla
MODEL: Model Y - 78,8 kWh

MILEAGE: 49,882 km
VIN: LRWYHCEL0PC726639
DATE AND TIME: 20/11/2026, 14:11

EXECUTED BY: Carma

RESULTS

Independent
STATE OF HEALTH (SOH)


92.2 %

ENERGY 73kWh | 79kWh

WLTP RANGE 573km | 622km

RATING

BENCHMARKING
How does your vehicle compare to comparable vehicles?



below average | average | above average

CHECKS

- Battery Management System (BMS) ✓
- Battery Sensor ✓
- Battery Measurements ✓
- Battery Cell Voltages ✓
- Vehicle Communication ✓

SCAN FOR DETAILS

EVALUATION

GOOD HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in good condition.

The drive battery is therefore officially AVILOO Certified.

Dr. Marcus Berger, CEO

CARA Approved Battery Health Check

BATTERY IS TESTED AND AVILOO CERTIFIED

AVILOO CERTIFIED

ENERGY

	Gross	Net (Nominal)	Usable
Current:	72.6kWh	72.6kWh	69.4kWh
New:	78.8kWh	78.8kWh	75.3kWh

RANGE

	WLTP	Typical	Individual
Current:	474-573km	370km	313km
New:	514-622km	401km	340km

EXECUTION PROTOCOL

AVILOO Box connected. **14:11:23**

- FLASH Test started. ✓
- Vehicle detected. ✓
- Data acquisition started. ✓
- Data acquisition completed. ✓
- Data analysis started. ✓
- Data analysis completed. ✓

SENSORS

- Voltage Sensor ✓
- Current Sensor ✓
- Temperature Sensors ✓
- Cell Voltage Sensors ✓

BMS


	Value	Status
BMS State of Charge (SoC)*:	38%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	90%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	30.5°C	31.0°C	0.5°C	✓
Cell Voltage	3.692V	3.698V	6mV	✓
Pack Voltage	355.0V			
Average Current	-3.6A			

CELL VOLTAGES DIAGRAM

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1 - 20	3.696	3.696	3.696	3.696	3.696	3.696	3.698	3.696	3.698	3.696	3.696	3.695	3.696	3.692	3.696	3.695	3.696	3.696	3.696	3.696
21 - 40	3.696	3.696	3.696	3.696	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695	3.695
41 - 60	3.695	3.695	3.695	3.695	3.695	3.695	3.694	3.695	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.698	3.698	3.698	3.698
61 - 80	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.698	3.698	3.698	3.698	3.698	3.698	3.698	3.696	3.696	3.696	3.696	3.696
81 - 96	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696	3.696				



*The values shown here were read directly from the vehicle's battery management system (BMS) and are calculated and provided by the vehicle manufacturer. The State of Health (SoH) displayed corresponds to the value reported by the BMS and is CARA-certified.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.

AVILOO GmbH | IZ NÖ-Süd, Straße 16, Objekt 69/5 | 2355 Wiener Neudorf | Austria | business.help@aviloo.com

A9E97F5F-09F5-412C-BC96-6AC7C622E1C1