

INDEPENDENT BATTERY CERTIFICATE



CERTIFICATE NUMBER: A73CF3D5-C9DA-4B8A-91C0-DC61D85A97EC

VEHICLE

BRAND: Mitsubishi
MODEL: Outlander PHEV - 13,8 kWh

MILEAGE: 58,990 km
VIN: JMFXDGG3WLZ001847
DATE AND TIME:
07/08/2026, 15:51

EXECUTED BY: Carma

RESULTS

Independent
STATE OF HEALTH (SOH)

71.3 %

ENERGY

7kWh | 10kWh




WLTP RANGE

38km | 54km

RATING

BENCHMARKING

How does your vehicle compare to comparable vehicles?



CHECKS

Battery Management System (BMS) ✓

Battery Sensor ✓

Battery Measurements ✓

Battery Cell Voltages ✓

Vehicle Communication ✓



SCAN FOR DETAILS

EVALUATION

FAIR HEALTH - NO ABNORMALITIES DETECTED

Based on the detailed battery diagnostics performed with the AVILOO FLASH Test, we hereby certify that the drive battery of this vehicle is in fair condition.

The drive battery is therefore officially AVILOO Certified.

Marcus Berger

Dr. Marcus Berger, CEO



ENERGY

	Gross	Net (Nominal)	Usable
Current:	9.8kWh	7.1kWh	7.1kWh
New:	13.8kWh	10.0kWh	10.0kWh

RANGE

	WLTP	Typical
Current:	38km	30km
New:	54km	42km

EXECUTION PROTOCOL

AVILOO Box connected. 15:51:25

FLASH Test started.	✓
Vehicle detected.	✓
Starting data acquisition.	✓
Finished data acquisition.	✓
Analyzing data.	✓
Analysis completed.	✓

SENSORS

Voltage Sensor	✓
Current Sensor	✓
Temperature Sensors	✓
Cell Voltage Sensors	✓

BMS


	Value	Status
BMS State of Charge (SoC)*:	29%	
SoC calculation accuracy:		✓
BMS State of Health (SoH)*:	70%	
SoH calculation accuracy:		✓

MEASUREMENTS

	Min	Max	Delta	Status
Battery Temperature	36.0°C	38.0°C	2.0°C	✓
Cell Voltage	3.826V	3.837V	11mV	✓
Pack Voltage	306.5V			
Average Current	-1.0A			

CELL VOLTAGES DIAGRAM

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1 - 20	3.831	3.830	3.831	3.831	3.831	3.831	3.832	3.833	3.832	3.829	3.829	3.828	3.827	3.828	3.830	3.832	3.831	3.830	3.831	3.830
21 - 40	3.831	3.830	3.831	3.835	3.835	3.831	3.830	3.830	3.830	3.829	3.830	3.832	3.832	3.831	3.832	3.830	3.830	3.833	3.833	3.837
41 - 60	3.836	3.833	3.833	3.832	3.829	3.830	3.829	3.833	3.835	3.829	3.833	3.832	3.828	3.833	3.832	3.837	3.835	3.833	3.831	3.831
61 - 80	3.832	3.831	3.832	3.833	3.832	3.829	3.826	3.831	3.827	3.828	3.829	3.833	3.835	3.833	3.833	3.831	3.830	3.833	3.833	3.833



*The values shown here were read directly from the vehicle's battery management system (BMS) and are calculated and provided by the vehicle manufacturer. The State of Health (SoH) displayed corresponds to the value reported by the BMS and is CARA-certified.

DISCLAIMER: The test result includes the currently calculated state of health (SoH) of the drive battery. The determination is based on data provided by the vehicle. These are evaluated by AVILOO's algorithms using statistical and analytical models. Manipulation of the data in the control unit leads to an incorrect result. The indicated SoH has a technically induced fluctuation range (deviation) of no more than 3% in at least 95% of reference measurements. It should be noted that this tolerance applies to the SoH determination at the cell level and not to the SoH of the entire battery. This is because the state of charge of individual cells may vary, which can negatively affect the current SoH of the battery. However, this can be compensated by the Battery Management System (BMS) or during a calibration. The result reflects the condition of the battery at the time of the test. No conclusions can be drawn about the future state of health of the battery from this. Statements about mechanical damage or external influences are not part of this diagnosis.